

SCM-21A



Face



Back



Menu

Features

SCM-21A PROGRESSIVE DIGITAL COLOUR MONITOR	
CRT	21 inches 0.28 fine adjustment pure flat CRT
Video input/output	2 channels BNC input/1 channel BNC output, 1 channel VGA, YCbCr, S terminal input/output
Audio input/output	4 channels RCA input/1 channel RCA output
Panel Control	Menu (Contrast, Brightness, Sharpness, Color, Color mode Volume, power
Power source	Ranged from 100—230V AC
Power consumption	Max: 85W
Dimension	492mm x 445mm x 480mm (W x H x D)
Weight (N.W.)	27 Kilograms
Resolution	Max: NTSC 1040 lines, PAL 1250 lines
VGA interface definition	VGA 640 x 480
Audio frequency	Max: 3W
Operating temperature	0°C ~ 50°C
Operating humidity	10 ~ 90%

SCM-14N



Face



Back



Menu

Features

SCM-14N COLOUR MONITOR	
Video input/output	BNC interface input/output
Panel Control	Bright, Contrast, Color saturation, Tint*, Power
Power source	Ranged from 100~230V AC
Power consumption	Max:60W
Dimension	366mm×342mm×392mm(W×H×D)
Weight(N.W.)	12 Kilograms
Resolution	Max:NTSC 380 lines、 PAL 450 lines
Horizontal stabilization	15.625KHz ±500Hz
Vertical stabilization	50Hz/60Hz ±3Hz
Operating temperature	0°C~50°C
Operating humidity	10~90%
* Just for NTSC system	

SCM-12H



Face



Back



Menu

Features

SCM-12H BLACK AND WHITE MONITOR	
CRT	12 inches
Video input/output	BNC interface input/output
Panel Control	H-Hold, V-Hold, Contrast, Bright, Power on/off
Power source	Ranged from 100-230V AC
Power consumption	Max:40W
Dimension	305mmx298mmx315mm(WxHxD)
Weight(N.W.)	9.5 Kilograms
Resolution	Max:1000 lines
Horizontal stabilization	15.625KHz \pm 500Hz
Vertical stabilization	50Hz/60Hz \pm 3Hz
Operating temperature	0°C~50°C
Operating humidity	10~90%

